

## Rebuild Grinders

### Centerless Grinder

#### 4520C



#### Rebuilding

Manufactured in 1995

G.W. O.D. : Max.  $\phi 455$  mm

Width : Max. 205 mm

Grinding method : In-feed/  
Through-feed

Grinding range :  $\phi 1 \sim \phi 40$  mm

Half-year warranty

### Double Disc Grinder

#### KVD300



#### Rebuilt machine

Manufactured in 1998

G.W O.D. : Max.  $\phi 305$  mm

Thickness : Max. 50 mm

Rotational speed : Max.  $1,500 \text{ min}^{-1}$

Grinding method : Contact us for details.

O.D. : Max.  $\phi 50$  mm

Thickness : Max. 50 mm

Half-year warranty

### Single Disc Grinder

#### R632



#### Rebuilt machine

Manufactured in 1997

G.W. O.D. : Max.  $\phi 305$  mm

Thickness : Max. 50 mm

Rotational speed : Max.  $1,500 \text{ min}^{-1}$

Grinding O.D. : Max.  $\phi 125$  mm

range Thickness : Max. 35 mm

Half-year warranty

A rebuild machine is a machine that overhauls an old machine or an unused machine that we have taken over.

※ The machine photo is an image. Contact us for more details.

The next page is the "Surface Grinder" and "Internal Grinder".

## Rebuild Grinders

### Double Disc Grinder

#### HD5



#### Rebuilding

Manufactured in 1990

G.W O.D. : Max.  $\phi$  585 mm

Thickness : Max. 50 mm

Rotational speed : Max. 900 min<sup>-1</sup>

Grinding O.D. : Max.  $\phi$  150 mm

range Thickness : Max. 50 mm

Half-year warranty

## Contact Us

Overseas Sales Department

2-34 Minami Uematsu-Cho Yao-City, Osaka 581-0091 Japan

Phone : +81-72-922-7010

Please also use the inquiry form on our website.



Caution

- Some of our products are strategic products as defined in the Foreign Exchange and Foreign Trade Law of Japan. Export of those products requires an export license from the Japanese Government.
- All technical descriptions and specifications are subject to revision or correction without prior notice.